CS 61B Homework 4
Due 3pm Wednesday, February 23, 2000

This homework will give you practice with writing doubly-linked lists and using subclasses. This is an individual assignment; you may not share code with other students.

Copy the Homework 4 directory by doing the following, starting from your home directory. Don't forget the "-r" switch in the cp command.

```
mkdir hw4
cd hw4
cp -r $master/hw/hw4/* .
```

When you did Project 1, you probably noticed that the SList ADT doesn't allow you to walk through an SList and process each node as you go. Either you must violate the ADT by manipulating the SList pointers directly, or you must use the slow nth() method to access each successive element, thereby obtaining a toOcean() method that runs in time proportional to N^2, where N is the size of the list. Because we didn't know about Java packages, we were unable to develop a really satisfying list ADT.

In this homework, you will implement a doubly-linked list ADT that allows an application to hold list nodes and hop from node to node quickly. How do we make the list an ADT if applications can get access to list nodes? It's easy: we put all the list code in a package called "list", and we declare the fields of DListNode protected--except the "item" field, which is public. Applications can't access the "prev" or "next" fields of a DListNode, so they can't violate any List invariants.

The "item" field is public because it doesn't take part in invariants. Applications may read and change it as they please. In fact, no method is provided for reading the "item" field indirectly.

Part I (6 points)

DList.java contains a skeleton of a doubly-linked list class. Fill in the method implementations.

Your DList should be circularly-linked, and its head should be a sentinel node (which holds no item) as described in Lecture 8. An empty DList is signified by a sentinel node that points to itself. Some DList methods return DListNodes; they should never return the sentinel under any circumstances. Your DList should satisfy the following invariants.

1) head != null.
2) For any DListNode x in a DList, x.next != null and x.prev != null.
3) For any DListNode x in a DList, if x.next == y, then y.prev == x.
4) For any DListNode x in a DList, if x.prev == y, then y.next == x.
5) The "size" field is the number of DListNodes, excepting the sentinel, that can be accessed from the sentinel by a sequence of "next" references.

The DList class includes a newNode() method whose sole purpose is to call the DListNode constructor. All of your methods that insert a new node should call this method; they should not call the DListNode constructor directly. This will help minimize the number of methods you need to override in Part III.

Do not change any of the method prototypes; as usual, our test code expects you to adhere to the interface we provide. Do not change the fields of DList or DListNode. You may add helper methods as you please.

You may put any test code you like in main(). It will not be graded. We'll be testing your DList class, so you should too.

A quirk of Java is that you must compile and run your code from outside the list/ directory using the following syntax.

```
javac -g list/DListNode.java
java list.DListNode
```

Part II (1 point)

Our ADT is not as well protected as we would like. There are several ways by which a hostile (or stupid) application can corrupt our DList (i.e., make it violate an invariant) through method calls alone. Describe one in your GRADER file.

Part III (3 points)

Implement a "lockable" doubly-linked list ADT: a list in which any node can be "locked." A locked node can never be removed from its list. Any attempt to remove a locked node has no effect (not even an error message). Your locked list classes should be in the list package alongside DList and DListNode.

First, define a LockDListNode class that extends DListNode and carries information about whether it has been locked. LockDListNodes are not locked when they are first created. Your SafeDListNode constructor(s) should include a call to the DListNode constructor to avoid code duplication.

Second, define a LockDList class that extends DList and includes an additional method

```
public void lockNode(DListNode node) { ... }
```

that permanently locks "node".

Your LockDList should override whatever methods are necessary to ensure that
(1) LockDListNodes are used instead of DListNodes, and
(2) locked nodes cannot be removed from a list.

Your overriding methods should include calls to the overridden superclass methods whenever it makes sense to do so. Unnecessary code duplication will be penalized.

Again, I recommend you test your code.

Submitting your solution

Change (cd) to your hw4 directory, which should contain GRADER and the list directory. The list directory should contain DList.java, DListNode.java, LockDList.java, LockDListNode.java, and any other files needed to run your methods.

Your GRADER file should include your name, login, lab section, and answer to Part II. Include also any other comments you would like to make to the grader, such as parts of your solution that you know are not correct. From your hw4 directory, type "submit hw4".

After submitting, if you realize your solution is flawed, you may fix it and submit again. You may submit as often as you like. Only the last version you submit before the deadline will be graded.