

Universal instantiation (UI)

Every instantiation of a universally quantified sentence is entailed by it:

$$\frac{\forall v \alpha}{\text{SUBST}(\{v/g\}, \alpha)}$$

for any variable v and ground term g

E.g., $\forall x \text{ King}(x) \wedge \text{Greedy}(x) \Rightarrow \text{Evil}(x)$ yields

$$\begin{aligned} & \text{King}(\text{John}) \wedge \text{Greedy}(\text{John}) \Rightarrow \text{Evil}(\text{John}) \\ & \text{King}(\text{Richard}) \wedge \text{Greedy}(\text{Richard}) \Rightarrow \text{Evil}(\text{Richard}) \\ & \text{King}(\text{Father}(\text{John})) \wedge \text{Greedy}(\text{Father}(\text{John})) \Rightarrow \text{Evil}(\text{Father}(\text{John})) \\ & \vdots \end{aligned}$$

Outline

- ◇ Reducing first-order inference to propositional inference
- ◇ Unification
- ◇ Generalized Modus Ponens
- ◇ Forward and backward chaining
- ◇ Logic programming
- ◇ Resolution

Existential instantiation (EI)

For any sentence α , variable v , and constant symbol k that does not appear elsewhere in the knowledge base:

$$\frac{\exists v \alpha}{\text{SUBST}(\{v/k\}, \alpha)}$$

E.g., $\exists x \text{ Crown}(x) \wedge \text{OnHead}(x, \text{John})$ yields

$$\text{Crown}(C_1) \wedge \text{OnHead}(C_1, \text{John})$$

provided C_1 is a new constant symbol, called a Skolem constant

Another example: from $\exists x d(x^y)/dy = x^y$ we obtain

$$d(e^y)/dy = e^y$$

provided e is a new constant symbol

A brief history of reasoning

450B.C.	Stoics	propositional logic, inference (maybe)
322B.C.	Aristotle	"syllogisms" (inference rules), quantifiers
1565	Cardano	probability theory (propositional logic + uncertainty)
1847	Boole	propositional logic (again)
1879	Frege	first-order logic
1922	Wittgenstein	proof by truth tables
1930	Gödel	\exists complete algorithm for FOL
1930	Herbrand	complete algorithm for FOL (reduce to propositional)
1931	Gödel	$\neg\exists$ complete algorithm for arithmetic
1960	Davis/Putnam	"practical" algorithm for propositional logic
1965	Robinson	"practical" algorithm for FOL—resolution

Existential instantiation contd.

UI can be applied several times to **add** new sentences; the new KB is logically equivalent to the old

EI can be applied once to **replace** the existential sentence; the new KB is **not** equivalent to the old, but is satisfiable iff the old KB was satisfiable

Reduction to propositional inference

Suppose the KB contains just the following:

$\forall x \text{ King}(x) \wedge \text{Greedy}(x) \Rightarrow \text{Evil}(x)$
 $\text{King}(\text{John})$
 $\text{Greedy}(\text{John})$
 $\text{Brother}(\text{Richard}, \text{John})$

Instantiating the universal sentence in **all possible** ways, we have

$\text{King}(\text{John}) \wedge \text{Greedy}(\text{John}) \Rightarrow \text{Evil}(\text{John})$
 $\text{King}(\text{Richard}) \wedge \text{Greedy}(\text{Richard}) \Rightarrow \text{Evil}(\text{Richard})$
 $\text{King}(\text{John})$
 $\text{Greedy}(\text{John})$
 $\text{Brother}(\text{Richard}, \text{John})$

The new KB is **propositionalized**: proposition symbols are

$\text{King}(\text{John}), \text{Greedy}(\text{John}), \text{Evil}(\text{John}), \text{King}(\text{Richard})$ etc.

Unification

We can get the inference immediately if we can find a substitution θ such that $\text{King}(x)$ and $\text{Greedy}(x)$ match $\text{King}(\text{John})$ and $\text{Greedy}(y)$

$\theta = \{x/\text{John}, y/\text{John}\}$ works

$\text{UNIFY}(\alpha, \beta) = \theta$ if $\alpha\theta = \beta\theta$

p	q	θ
$\text{Knows}(\text{John}, x)$	$\text{Knows}(\text{John}, \text{Jane})$	
$\text{Knows}(\text{John}, x)$	$\text{Knows}(y, \text{OJ})$	
$\text{Knows}(\text{John}, x)$	$\text{Knows}(y, \text{Mother}(y))$	
$\text{Knows}(\text{John}, x)$	$\text{Knows}(x, \text{OJ})$	

Reduction contd.

Claim: a ground sentence* is entailed by new KB iff entailed by original KB

Claim: every FOL KB can be propositionalized so as to preserve entailment

Idea: propositionalize KB and query, apply resolution, return result

Problem: with function symbols, there are infinitely many ground terms, e.g., $\text{Father}(\text{Father}(\text{Father}(\text{John})))$

Theorem: Herbrand (1930). If a sentence α is entailed by an FOL KB, it is entailed by a **finite** subset of the propositional KB

Idea: For $n = 0$ to ∞ do
 create a propositional KB by instantiating with depth- n terms
 see if α is entailed by this KB

Problem: works if α is entailed, loops if α is not entailed

Theorem: Turing (1936), Church (1936), entailment in FOL is **semidecidable**

Unification

We can get the inference immediately if we can find a substitution θ such that $\text{King}(x)$ and $\text{Greedy}(x)$ match $\text{King}(\text{John})$ and $\text{Greedy}(y)$

$\theta = \{x/\text{John}, y/\text{John}\}$ works

$\text{UNIFY}(\alpha, \beta) = \theta$ if $\alpha\theta = \beta\theta$

p	q	θ
$\text{Knows}(\text{John}, x)$	$\text{Knows}(\text{John}, \text{Jane})$	$\{x/\text{Jane}\}$
$\text{Knows}(\text{John}, x)$	$\text{Knows}(y, \text{OJ})$	
$\text{Knows}(\text{John}, x)$	$\text{Knows}(y, \text{Mother}(y))$	
$\text{Knows}(\text{John}, x)$	$\text{Knows}(x, \text{OJ})$	

Problems with propositionalization

Propositionalization seems to generate lots of irrelevant sentences.

E.g., from

$\forall x \text{ King}(x) \wedge \text{Greedy}(x) \Rightarrow \text{Evil}(x)$
 $\text{King}(\text{John})$
 $\forall y \text{ Greedy}(y)$
 $\text{Brother}(\text{Richard}, \text{John})$

it seems obvious that $\text{Evil}(\text{John})$, but propositionalization produces lots of facts such as $\text{Greedy}(\text{Richard})$ that are irrelevant

With p k -ary predicates and n constants, there are $p \cdot n^k$ instantiations

With function symbols, it gets such much worse!

Unification

We can get the inference immediately if we can find a substitution θ such that $\text{King}(x)$ and $\text{Greedy}(x)$ match $\text{King}(\text{John})$ and $\text{Greedy}(y)$

$\theta = \{x/\text{John}, y/\text{John}\}$ works

$\text{UNIFY}(\alpha, \beta) = \theta$ if $\alpha\theta = \beta\theta$

p	q	θ
$\text{Knows}(\text{John}, x)$	$\text{Knows}(\text{John}, \text{Jane})$	$\{x/\text{Jane}\}$
$\text{Knows}(\text{John}, x)$	$\text{Knows}(y, \text{OJ})$	$\{x/\text{OJ}, y/\text{John}\}$
$\text{Knows}(\text{John}, x)$	$\text{Knows}(y, \text{Mother}(y))$	
$\text{Knows}(\text{John}, x)$	$\text{Knows}(x, \text{OJ})$	

Unification

We can get the inference immediately if we can find a substitution θ such that $King(x)$ and $Greedy(x)$ match $King(John)$ and $Greedy(y)$

$\theta = \{x/John, y/John\}$ works

$UNIFY(\alpha, \beta) = \theta$ if $\alpha\theta = \beta\theta$

p	q	θ
$Knows(John, x)$	$Knows(John, Jane)$	$\{x/Jane\}$
$Knows(John, x)$	$Knows(y, OJ)$	$\{x/OJ, y/John\}$
$Knows(John, x)$	$Knows(y, Mother(y))$	$\{y/John, x/Mother(John)\}$
$Knows(John, x)$	$Knows(x, OJ)$	

Soundness of GMP

Need to show that

$$p_1', \dots, p_n', (p_1 \wedge \dots \wedge p_n \Rightarrow q) \models q\theta$$

provided that $p_i'\theta = p_i\theta$ for all i

Lemma: For any definite clause p , we have $p \models p\theta$ by UI

1. $(p_1 \wedge \dots \wedge p_n \Rightarrow q) \models (p_1 \wedge \dots \wedge p_n \Rightarrow q)\theta = (p_1\theta \wedge \dots \wedge p_n\theta \Rightarrow q\theta)$
2. $p_1', \dots, p_n' \models p_1' \wedge \dots \wedge p_n' \models p_1'\theta \wedge \dots \wedge p_n'\theta$
3. From 1 and 2, $q\theta$ follows by ordinary Modus Ponens

Unification

We can get the inference immediately if we can find a substitution θ such that $King(x)$ and $Greedy(x)$ match $King(John)$ and $Greedy(y)$

$\theta = \{x/John, y/John\}$ works

$UNIFY(\alpha, \beta) = \theta$ if $\alpha\theta = \beta\theta$

p	q	θ
$Knows(John, x)$	$Knows(John, Jane)$	$\{x/Jane\}$
$Knows(John, x)$	$Knows(y, OJ)$	$\{x/OJ, y/John\}$
$Knows(John, x)$	$Knows(y, Mother(y))$	$\{y/John, x/Mother(John)\}$
$Knows(John, x)$	$Knows(x, OJ)$	$fail$

Standardizing apart eliminates overlap of variables, e.g., $Knows(z_{17}, OJ)$

Example knowledge base

The law says that it is a crime for an American to sell weapons to hostile nations. The country Nono, an enemy of America, has some missiles, and all of its missiles were sold to it by Colonel West, who is American.

Prove that Col. West is a criminal

Generalized Modus Ponens (GMP)

$$\frac{p_1', p_2', \dots, p_n', (p_1 \wedge p_2 \wedge \dots \wedge p_n \Rightarrow q)}{q\theta} \quad \text{where } p_i'\theta = p_i\theta \text{ for all } i$$

p_1' is $King(John)$ p_1 is $King(x)$
 p_2' is $Greedy(y)$ p_2 is $Greedy(x)$
 θ is $\{x/John, y/John\}$ q is $Evil(x)$
 $q\theta$ is $Evil(John)$

GMP used with KB of definite clauses (exactly one positive literal)
 All variables assumed universally quantified

Example knowledge base contd.

... it is a crime for an American to sell weapons to hostile nations:

Example knowledge base contd.

... it is a crime for an American to sell weapons to hostile nations:
 $American(x) \wedge Weapon(y) \wedge Sells(x, y, z) \wedge Hostile(z) \Rightarrow Criminal(x)$
 Nono ... has some missiles

Example knowledge base contd.

... it is a crime for an American to sell weapons to hostile nations:
 $American(x) \wedge Weapon(y) \wedge Sells(x, y, z) \wedge Hostile(z) \Rightarrow Criminal(x)$
 Nono ... has some missiles, i.e., $\exists x Owns(Nono, x) \wedge Missile(x)$:
 $Owns(Nono, M_1)$ and $Missile(M_1)$
 ... all of its missiles were sold to it by Colonel West
 $\forall x Missile(x) \wedge Owns(Nono, x) \Rightarrow Sells(West, x, Nono)$
 Missiles are weapons:
 $Missile(x) \Rightarrow Weapon(x)$
 An enemy of America counts as "hostile":

Example knowledge base contd.

... it is a crime for an American to sell weapons to hostile nations:
 $American(x) \wedge Weapon(y) \wedge Sells(x, y, z) \wedge Hostile(z) \Rightarrow Criminal(x)$
 Nono ... has some missiles, i.e., $\exists x Owns(Nono, x) \wedge Missile(x)$:
 $Owns(Nono, M_1)$ and $Missile(M_1)$
 ... all of its missiles were sold to it by Colonel West

Example knowledge base contd.

... it is a crime for an American to sell weapons to hostile nations:
 $American(x) \wedge Weapon(y) \wedge Sells(x, y, z) \wedge Hostile(z) \Rightarrow Criminal(x)$
 Nono ... has some missiles, i.e., $\exists x Owns(Nono, x) \wedge Missile(x)$:
 $Owns(Nono, M_1)$ and $Missile(M_1)$
 ... all of its missiles were sold to it by Colonel West
 $\forall x Missile(x) \wedge Owns(Nono, x) \Rightarrow Sells(West, x, Nono)$
 Missiles are weapons:
 $Missile(x) \Rightarrow Weapon(x)$
 An enemy of America counts as "hostile":
 $Enemy(x, America) \Rightarrow Hostile(x)$
 West, who is American ...
 $American(West)$
 The country Nono, an enemy of America ...
 $Enemy(Nono, America)$

Example knowledge base contd.

... it is a crime for an American to sell weapons to hostile nations:
 $American(x) \wedge Weapon(y) \wedge Sells(x, y, z) \wedge Hostile(z) \Rightarrow Criminal(x)$
 Nono ... has some missiles, i.e., $\exists x Owns(Nono, x) \wedge Missile(x)$:
 $Owns(Nono, M_1)$ and $Missile(M_1)$
 ... all of its missiles were sold to it by Colonel West
 $\forall x Missile(x) \wedge Owns(Nono, x) \Rightarrow Sells(West, x, Nono)$
 Missiles are weapons:

Forward chaining algorithm

```

function FOL-FC-Ask(KB,  $\alpha$ ) returns a substitution or false
  repeat until new is empty
    new  $\leftarrow$  {}
    for each sentence r in KB do
      ( $p_1 \wedge \dots \wedge p_n \Rightarrow q$ )  $\leftarrow$  STANDARDIZE-APART(r)
      for each  $\theta$  such that  $(p_1 \wedge \dots \wedge p_n)\theta = (p'_1 \wedge \dots \wedge p'_n)\theta$ 
        for some  $p'_1, \dots, p'_n$  in KB
           $q' \leftarrow$  SUBST( $\theta, q$ )
          if  $q'$  is not a renaming of a sentence already in KB or new then do
            add  $q'$  to new
             $\phi \leftarrow$  UNIFY( $q', \alpha$ )
            if  $\phi$  is not fail then return  $\phi$ 
          add new to KB
  return false

```

Forward chaining proof

American(West) *Missile(M1)* *Owns(Nono,M1)* *Enemy(Nono,America)*

Chapter 9 25

Properties of forward chaining

Sound and complete for first-order definite clauses
(proof similar to propositional proof)


Datalog = first-order definite clauses + **no functions** (e.g., crime KB)
FC terminates for Datalog in poly iterations: at most $p \cdot n^k$ literals

May not terminate in general if α is not entailed

This is unavoidable: entailment with definite clauses is semidecidable

Chapter 9 28

Forward chaining proof



Chapter 9 26

Efficiency of forward chaining

Simple observation: no need to match a rule on iteration k
if a premise wasn't added on iteration $k - 1$

⇒ match each rule whose premise contains a newly added literal

Matching itself can be expensive


Database indexing allows $O(1)$ retrieval of known facts
e.g., query *Missile(x)* retrieves *Missile(M1)*

Matching conjunctive premises against known facts is NP-hard

Forward chaining is widely used in deductive databases


Chapter 9 29

Forward chaining proof



Chapter 9 27

Hard matching example



$Diff(wa, nt) \wedge Diff(wa, sa) \wedge$
 $Diff(nt, q) Diff(nt, sa) \wedge$
 $Diff(q, nsw) \wedge Diff(q, sa) \wedge$
 $Diff(nsw, v) \wedge Diff(nsw, sa) \wedge$
 $Diff(v, sa) \Rightarrow Colorable()$
 $Diff(Red, Blue) \quad Diff(Red, Green)$
 $Diff(Green, Red) \quad Diff(Green, Blue)$
 $Diff(Blue, Red) \quad Diff(Blue, Green)$


Colorable() is inferred iff the CSP has a solution
CSPs include 3SAT as a special case, hence matching is NP-hard

Chapter 9 30

Backward chaining algorithm

function FOL-BC-ASK($KB, goals, \theta$) **returns** a set of substitutions
inputs: KB , a knowledge base
 $goals$, a list of conjuncts forming a query (θ already applied)
 θ , the current substitution, initially the empty substitution $\{ \}$
local variables: $answers$, a set of substitutions, initially empty
if $goals$ is empty **then return** $\{ \theta \}$
 $q' \leftarrow \text{SUBST}(\theta, \text{FIRST}(goals))$
for each sentence r **in** KB
 where $\text{STANDARDIZE-APART}(r) = (p_1 \wedge \dots \wedge p_n \Rightarrow q)$
 and $\theta' \leftarrow \text{UNIFY}(q, q')$ succeeds
 $new_goals \leftarrow [p_1, \dots, p_n] \text{REST}(goals)$
 $answers \leftarrow \text{FOL-BC-ASK}(KB, new_goals, \text{COMPOSE}(\theta', \theta)) \cup answers$
return $answers$


Backward chaining example




Backward chaining example

Criminal(West)


Backward chaining example




Backward chaining example



Backward chaining example



Backward chaining example



Chapter 9 37

Logic programming


Sound bite: computation as inference on logical KBs

Logic programming	Ordinary programming
1. Identify problem	Identify problem
2. Assemble information	Assemble information
3. Tea break	Figure out solution
4. Encode information in KB	Program solution
5. Encode problem instance as facts	Encode problem instance as data
6. Ask queries	Apply program to data
7. Find false facts	Debug procedural errors

Should be easier to debug *Capital(NewYork,US)* than $x := x + 2$!

Chapter 9 40

Backward chaining example



Chapter 9 38

Prolog systems

Basis: backward chaining with Horn clauses + bells & whistles
Widely used in Europe, Japan (basis of 5th Generation project)
Compilation techniques \Rightarrow approaching a billion LIPS

Program = set of clauses = head :- literal₁, ... literal_n.

```
criminal(X) :- american(X), weapon(Y), sells(X,Y,Z), hostile(Z).
```

Efficient unification by **open coding**

Efficient retrieval of matching clauses by direct linking

Depth-first, left-to-right backward chaining

Built-in predicates for arithmetic etc., e.g., X is Y*Z+3

Closed-world assumption ("negation as failure")

```
e.g., given alive(X) :- not dead(X).
```

```
alive(joe) succeeds if dead(joe) fails
```

Chapter 9 41

Properties of backward chaining

Depth-first recursive proof search: space is linear in size of proof

Incomplete due to infinite loops

\Rightarrow fix by checking current goal against every goal on stack

Inefficient due to repeated subgoals (both success and failure)

\Rightarrow fix using caching of previous results (extra space!)

Widely used (without improvements!) for **logic programming**

Prolog examples

Depth-first search from a start state X:

```
dfs(X) :- goal(X).
```

```
dfs(X) :- successor(X,S),dfs(S).
```

No need to loop over S: successor succeeds for each

Appending two lists to produce a third:

```
append([],Y,Y).
```

```
append([X|L],Y,[X|Z]) :- append(L,Y,Z).
```

```
query: append(A,B,[1,2]) ?
```

```
answers: A=[] B=[1,2]
```

```
A=[1] B=[2]
```

```
A=[1,2] B=[]
```

Chapter 9 39

Chapter 9 42

Resolution: brief summary

Full first-order version:

$$\frac{\ell_1 \vee \dots \vee \ell_k, \quad m_1 \vee \dots \vee m_n}{(\ell_1 \vee \dots \vee \ell_{i-1} \vee \ell_{i+1} \vee \dots \vee \ell_k \vee m_1 \vee \dots \vee m_{j-1} \vee m_{j+1} \vee \dots \vee m_n)\theta}$$

where $\text{UNIFY}(\ell_i, \neg m_j) = \theta$.


For example,

$$\frac{\neg \text{Rich}(x) \vee \text{Unhappy}(x) \quad \text{Rich}(\text{Ken})}{\text{Unhappy}(\text{Ken})}$$

with $\theta = \{x/\text{Ken}\}$

Apply resolution steps to $\text{CNF}(KB \wedge \neg\alpha)$; complete for FOL

Resolution proof: definite clauses



Conversion to CNF

Everyone who loves all animals is loved by someone:

$$\forall x [\forall y \text{ Animal}(y) \Rightarrow \text{Loves}(x, y)] \Rightarrow [\exists y \text{ Loves}(y, x)]$$

1. Eliminate biconditionals and implications

$$\forall x [\neg \forall y \neg \text{Animal}(y) \vee \text{Loves}(x, y)] \vee [\exists y \text{ Loves}(y, x)]$$

2. Move \neg inwards: $\neg \forall x, p \equiv \exists x \neg p$, $\neg \exists x, p \equiv \forall x \neg p$:

$$\begin{aligned} &\forall x [\exists y \neg(\neg \text{Animal}(y) \vee \text{Loves}(x, y))] \vee [\exists y \text{ Loves}(y, x)] \\ &\forall x [\exists y \neg \neg \text{Animal}(y) \wedge \neg \text{Loves}(x, y)] \vee [\exists y \text{ Loves}(y, x)] \\ &\forall x [\exists y \text{ Animal}(y) \wedge \neg \text{Loves}(x, y)] \vee [\exists y \text{ Loves}(y, x)] \end{aligned}$$

Conversion to CNF contd.

3. Standardize variables: each quantifier should use a different one

$$\forall x [\exists y \text{ Animal}(y) \wedge \neg \text{Loves}(x, y)] \vee [\exists z \text{ Loves}(z, x)]$$

4. Skolemize: a more general form of existential instantiation.

Each existential variable is replaced by a **Skolem function** of the enclosing universally quantified variables:

$$\forall x [\text{Animal}(F(x)) \wedge \neg \text{Loves}(x, F(x))] \vee \text{Loves}(G(x), x)$$

5. Drop universal quantifiers:

$$[\text{Animal}(F(x)) \wedge \neg \text{Loves}(x, F(x))] \vee \text{Loves}(G(x), x)$$

6. Distribute \wedge over \vee :

$$[\text{Animal}(F(x)) \vee \text{Loves}(G(x), x)] \wedge [\neg \text{Loves}(x, F(x)) \vee \text{Loves}(G(x), x)]$$